LCD MODULE

SPECIFICATION

Model:	UE050FW-RB40-A111A
Version:	V1.0
Date:	20210810

JIANGXI VIEWE TECHNOLOGY CO.,LTD

Customer Confirmation 客户确认

Approved by	Notes

Please return one of the copies of the specification with your signature to us within two weeks after you receive this document. If it is not returned, we will assume that you agree to the entire contents of this specification document.

请贵司在收到规格书的两周内，将签好字的规格书原件或者复印件寄回.如果没有返回，我司将会认为贵司已经默认接受产品规格书中的全部资料和规范.

VIEWE Confirmation 优奕确认

Prepared by	Reviewed by	Approved by

REVISION HISTORY

Revision 版本号	Date 日期	Contents of Revision Change 修改内容	Remark 备注
V1.0	20210810	Preliminary release	

JIANGXI VIEWE TECHNOLOGY CO.,LTD

TABLE of CONTENTS

1. GENERAL INFORMATION....4
1.1 Features....4
1.2 Mechanical Specification....4
2. ABSOLUTE MAXIMUM RATINGS....5
3. MECHANICAL DRAWING....6
4. I/O CONNECTION & BLOCK DIAGRAM....7
4.1 I/O Connection....7
4.2 Block Diagram....8
5. ELECTRICAL CHARACTERISTICS....9
5.1 TFT-LCD Panel Driving Section....9
5.2 Back Light Driving Section....9
5.3 Power On/Off Sequence....10
5.3.1 LCM RESX line is held high or unstable by host at power on....11
5.3.2 LCM RESX line is held low by host at power on....12
5.3.3 Abnormal Power Off....13
5.3.4 TP....13
5.4 AC characteristics....16
5.4.1 Display Serial Interface Timing Characteristics (3-line SPI system)....16
5.4.2 Parallel 24/18/16-bit RGB Interface Timing Characteristics....17
5.5 Timing Diagram....18
5.5.1 DPI Interface Timing....18
5.5.2 Porch....19
6. OPTICAL CHARACTERISTICS....20
7. RELIABILITY....23
8. PACKAGE DRAWING....24

JIANGXI VIEWE TECHNOLOGY CO.,LTD

1. GENERAL INFORMATION

1.1 Features

1) Pixel Arrangement：RGB Vertical Stripe
2) Interface Mode：3 wire SPI+RGB 18bits
3) Driver IC：GC9503V ； TP Driver：CHSC6540
4) Operation Temperature：-20~70℃
5) Storage Temperature：-30~80℃
6) Backlight Type：White LED
7) Display mode：Normally Black
8) Pixel Density：197 PPI
9) LED life time：30,000 Hours

1.2 Mechanical Specification

Item 项目	Specification 规格	Unit 单位	Remark 备注
Pixel Driving element	IPS TFT	-	-
Screen Size	4.95	Inch	Diagonal
Resolution	480(W)*3(RGB)*854(H)	Dots	-
Interface	3 wire SPI+RGB 18bits	-	4 lanes
Module Power Consumption	0.928	Watt	Typ.
Active Area	61.56(W)*109.53(H)	mm	-
Pixel pitch (W*H)	42.75(W)*128.25(H)	mm	-
Module Size (W*H*D)	68.1(W)*121.05(H)*3.5(D)	mm	Typ
Luminance	250	cd/m^2	Typ.
Viewing Direction	ALL	O'clock	
Display Color	16.7M	Colors	24bits

JIANGXI VIEWE TECHNOLOGY CO.,LTD

2. ABSOLUTE MAXIMUM RATINGS

Item 项目	Symbol 符号	Min. 最小值	Max. 最大值	Unit 单位	Remark 备注
Power supply1 voltage	TP_VCI	-0.3	3.6	V	Note1
Power supply2 voltage	VCI	-0.3	4.6	V	Note1
LED Reverse Voltage	V_R	-	5	V	For each led,Note1
Operating temperature	T_{op}	-20	70	℃	Note1,2
Storage temperature	T_{st}	-30	80	℃	Note1,2
Humidity	H_{st}	10	90	%RH	Note1,3

(Ta=+25°C,GND=0V)

Note1:If the module exceeds the absolute maximum ratings, it may be damaged permanently. Also if the module operates with the absolute maximum ratings for a long time, the reliability may drop.

Note2: In case of temperature below 0℃,the response time of liquid crystal (LC) becomes slower and the color of panel darker than normal one.

Note3: Temp. ≤ 60℃ , 90% RH MAX.

Temp. ＞60℃ , Absolute humidity shall be less than 90% RH at 60℃.

JIANGXI VIEWE TECHNOLOGY CO.,LTD

3. MECHANICAL DRAWING



JIANGXI VIEWE TECHNOLOGY CO.,LTD

4. I/O CONNECTION & BLOCK DIAGRAM

4.1 I/O Connection

Pin No. 序号	Symbol 符号	I/O	Description 描述
1	**LEDA**	P	Power supply for backlight anode
2	**LEDK1**	P	Power supply for backlight cathode
3	**LEDK2**	P	Power supply for backlight cathode
4	**GND**	P	Power Ground
5	**VCI**	P	Power supply for analog circuits
6	**RESET**	I	The signal will reset the LCM, Signal is active low.
7-8	**NC**	-	No connected
9	**SDA**	I/O	Data select pin for SPI interface
10	**SCK**	I	Clock select pin for SPI interface
11	**CS**	I	Chip select pin for SPI interface
12	**PCLK**	I	Dot clock signal for RGB interface operation
13	**DE**	I	Data input enable. Display access is enabled when DE is "H"
14	**VSYNC**	I	Vertical sync signal, Negative polarity
15	**HSYNC**	I	Horizontal sync signal, Negative polarity
16-21	**B0-B5**	I	Blue data input.
22-27	**G0-G5**	I	Green data input.
28-33	**R0-R5**	I	Red data input.
34	**GND**	P	Power Ground
35	**TP_INT**	O	Interrupt signals for TP
36	**TP_SDA**	I/O	I2C data signal for TP
37	**TP_SCL**	I	I2C clock signals for TP
38	**TP_RESET**	I	The signal will reset the TP,Signal is active low
39	**TP_VCI**	P	Power supply for TP
40	**GND**	P	Power Ground

I：Input；O：Output；P：Power

JIANGXI

4.2 Block Diagram



5. ELECTRICAL CHARACTERISTICS

5.1 TFT-LCD Panel Driving Section

Item 项目	Symbol 符号	Min. 最小值	Typ. 典型值	Max. 最大值	Unit 单位	Remark 备注
Power Supply1 Voltage	TP_VCI	2.6	2.8	3.6	V	-
Power Supply2 Voltage	VCI	2.5	2.8	3.3	V	-
Power Supply1 Current	I_{TP_VCI}	-	7	-	mA	Note1
Power Supply2 Current	I_{VCI}	-	50	-	mA	Note1
Logic Input High Voltage	V_{IH}	0.7VCI	-	VCI	V	-
Logic Input Low Voltage	V_{IL}	0	-	0.3VCI	V	-
Panel Power Consumption	P_{VDD}	-	0.16	-	Watt	Note1
Module Power Consumption	P_{ALL}	-	0.928	-	Watt	Note1,2

(Ta=+25°C,GND=0V)

Note1:Measurement Conditions (Video Mode): Full Screen Red Pattern,VDD=1.8V,60Hz Refresh.

Note2: P_{ALL}= P_{VDD}+ P_{BL}， About P_{BL} information, inference to 5.2 Back Light Driving Section.

5.2 Back Light Driving Section

Item 项目	Symbol 符号	Min. 最小值	Typ. 典型值	Max. 最大值	Unit 单位	Remark 备注
Forward Voltage	V_F	-	19.2	-	V	Note1
Forward Current	I_F	-	40	-	mA	Note1
Backlight Power consumption	P_{BL}	-	0.768	-	Watt	Note1
LED life time	-	30000	-	-	Hours	Note2
LED Quantity			12		PCS	

(Ta=+25°C,GND=0V)

Note1:The “LED life time” is defined as the module brightness decrease to 50% of original brightness at I_{LED}=20mA(Per Led). The LED life time could be decreased if operating I_{LED} is larger than 20mA.



JIANGXI VIEWE TECHNOLOGY CO.,LTD

5.3 Power On/Off Sequence

IOVCC and VCI can be applied (or powered down) in any order. During the power off sequences, if LCD is in the Sleep Out mode, VCI and IOVCC must be powered down with minimum 120msec, and if LCD is in the Sleep In mode, VCI and IOVCC can be powered down with minimum 0msec after RESX has been released.
CSX can be applied at any timing or can be permanently grounded. RESX has priority over CSX.

Note:

1. There will be no damage to GC9503V if the power sequences are not met.
2. There will be no abnormal visible effects on the display panel during the Power On/Off Sequences.
3. There will be no abnormal visible effects on the display between end of Power On Sequence and before receiving Sleep Out command. Also between receiving Sleep In command and Power Off Sequence.
4. If RESX line is not held stable by host during Power On Sequence as defined in Sections 7.1 and 7.2, then it will be necessary to apply a Hardware Reset (RESX) after Host Power On Sequence is complete to ensure correct operation. Otherwise function is not guaranteed.
5. Keep data pins DB[23:0] at low level, when VCIP or IOVCC comes later



5.3.1 LCM RESX line is held high or unstable by host at power on

If the RESX line is held high or unstable by the host during Power On, then a Hardware Reset must be applied after both VCI and IOVCC have been applied – otherwise correct functionality is not guaranteed. There is no timing restriction upon this hardware reset.



trPWRESX1 is applied to RESX falling in the Sleep Out Mode

trPWRESX2 is applied to RESX falling in the Sleep In Mode

JIANGXI VIEWE Xycore

5.3.2 LCM RESX line is held low by host at power on

If the RESX line is held Low (and stable) by the host during Power On, then the RESX must be held low for minimum 10µsec after both VCI and IOVCC have been applied.



trPWRESX1 is applied to RESX falling in the Sleep Out Mode
trPWRESX2 is applied to RESX falling in the Sleep In Mode

Figure 99 Case 2 – RESX line is held Low by Host at Power ON

Note: 1. Unless otherwise specified, timings herein show cross point at 50% of signal power level.

JIANGXI VIEWE OPTOELECTRONIC

5.3.3 Abnormal Power Off

The abnormal power off means a situation when e.g. there is removed a battery without the normal power off sequence. There will not be any damages for the display module or the display module will not cause any damages for the host or lines of the interface. At an abnormal power off event, GC9503V will force the display to blank and will not be any abnormal visible effects with in 1 second on the display and remains blank until "Power On Sequence" powers it up

5.3.4 TP

Reset should be pulled down to be low before powering on and powering down. I2C shouldn't be used by other devices during Reset time after VDD powering on (Trtp). INT signal will be sent to the host after ini- tializing all parameters and then start to report points to the host. If Power is down, the voltage of supply must be below 0.3V and Tpdt is more than 1ms.



Figure 8.1 power on time



Figure 8-2 Power Cycle requirement



Figure 8-3 Power on Sequence

Reset time must be enough to guarantee reliable reset, the time of starting to eport point after resetting approach to the time of starting to report point after powering on.



Figure 8.4 Reset Sequence

Table 8-1 Power on/Reset Sequence Parameters

Parameter	Description	Min	Max	Units
Tris	Rise time from 0.1VDD to 0.9VDD	--	5	ms
Tpdt	Time of the voltage of supply being below 0.3V	2	--	ms
Trtp	Time of resetting to be low before powering on	100	--	μs
Tpon	Time of starting to report point after powering on	--	200	ms
Tvdr	Reset time after VDD powering on	1	--	ms
Trsi	Time of starting to report point after resetting	--	200	ms
Trst	Reset time	500	--	us

JIANGXI VIEWE TEC

5.4 AC characteristics

5.4.1 Display Serial Interface Timing Characteristics (3-line SPI system)



Signal	Symbol	Parameter	min	max	Unit	Description
CSX	tcss	Chip select time (Write)	15	-	ns	
	tcsh	Chip select hold time (Read)	15	-	ns	
	tCHW	CS "H" pulse width	40	-	ns	
SCL	twc	Serial clock cycle (Write)	30	-	ns	
	twrh	SCL "H" pulse width (Write)	10	-	ns	
	twrl	SCL "L" pulse width (Write)	10	-	ns	
	trc	Serial clock cycle (Read)	150	-	ns	
	trdh	SCL "H" pulse width (Read)	60	-	ns	
	trdl	SCL "L" pulse width (Read)	60	-	ns	
SDA/SDO (Output)	tacc	Access time (Read)	10	100	ns	For maximum CL=30pF
	toh	Output disable time (Read)	15	100	ns	For minimum CL=8pF
SDA/SDI (Input)	tds	Data setup time (Write)	10	-	ns	
	tdh	Data hold time (Write)	10	-	ns	

Note:

1. Ta = -30 to 70 °C, IOVCC=1.65V to 3.6V, VCI=2.5V to 3.6V, T=10+/-0.5ns.
2. Does not include signal rise and fall times.

5.4.2 Parallel 24/18/16-bit RGB Interface Timing Characteristics



Signal	Symbol	Parameter	min	max	Unit	Description
VS/ HS	t_{SYNCS}	VS/HS setup time	5	-	ns	24/18/16-bit bus RGB interface mode
	t_{SYNCH}	VS/HS hold time	5	-	ns	
DE	t_{ENS}	DE setup time	5	-	ns	
	t_{ENH}	DE hold time	5	-	ns	
DB[23:0]	t_{POS}	Data setup time	5	-	ns	
	t_{PDH}	Data hold time	5	-	ns	
PCLK	PWDH	PCLK high-level period	13	-	ns	
	PWDL	PCLK low-level period	13	-	ns	
	t_{CYCD}	PCLK cycle time	28	-	ns	
	t_{rgbr} , t_{rgbf}	PCLK,HS,VS rise/fall time	-	15	ns	

Note: Ta = -30 to 70 °C, IOVCC=1.65V to 3.6V, VCI=2.5V to 3.6V, DGND=0V

JIANGXI VIEWE

5.5 Timing Diagram

5.5.1 DPI Interface Timing



VLW : VSYNC Low pulse Width
HLW : HSYNC Low pulse Width
DTST : Data Transfer Startup Time
Pn : pixel 1, pixel 2…, pixel n.

Parameter	Symbol	Conditio	Min	Typ	Max	Units
Frame Rate	FR		54		6	fps
Horizontal Low Pulse width	HLW		1		-	DOTCL
Horizontal Back Porch	HBP		2		126	DOTCL
Horizontal Address	HACT			48		DOTCL
Horizontal Front Porch	HFP		2		-	DOTCL
Vertical Low Pulse width	VLW		1		126	Line
Vertical Back Porch	VBP		1		126	Line
Vertical Address	VACT				864	Line
Vertical Front Porch	VFP		1		255	Line
Data Clock	DCLK		16.		35.	MHz

Figure 12 DPI Interface Timing diagram[Note1,Note2]

5.5.2 Porch



6. OPTICAL CHARACTERISTICS

Parameter 参数	Symbol 符号	Condition 条件	Min. 最小值	Typ. 典型值	Max. 最大值	Unit 单位	Remark 备注
Contrast Ratio	C/R	θ = 0°	1000	1500	-	-	Note(4)
NTSC Ratio	S	θ =0°	61.9	66.9		%	Note(7)
Luminance	L	θ =0°	200	250	-	cd/m2	Note(5)
Luminance uniformity	Uw	θ =0°	80	-	-	%	Note(3)
Response Time	T_R+ T_F	25 °C	-	30	35	ms	Note(2)
Color Coordination	Wx	θ =s 0° (Center) Normal viewing angle B/L On	-0.04	0.3	+0.04	NTSC (x,y)	Note(6)
	Wy			0.32			
	Rx			0.659			
	Ry			0.323			
	Gx			0.276			
	Gy			0.581			
	Bx			0.134			
	By			0.125			
Viewing Angle	θ L	C/R>10	70	80	-	Degree	Note(1)
	θ R		70	80	-		
	θ U		70	80	-		
	θ D		70	80	-		

Test Conditions:

1. the ambient temperature is+25℃.
2. The test systems refer to Note 8.

JIANGXI VIEWE TECHNOLOGY CO.,LTD

Note1: Definition of Viewing Angle: The viewing angle range that the CR>10



Note2: Definition of Response time: Sum of T_R and T_F



Note 3: Definition of Luminance Uniformity: Active area is divided into 9 measuring areas, every measuring point is placed at the center of each measuring area.

$$\text{Luminance Uniformity} = \frac{\text{Min Luminance of white among 9-points}}{\text{Max Luminance of white among 9-points}} \times 100\%$$



Note4: Definition of Contrast Ratio (CR): measured at the center point of panel

$$\text{Contrast ratio (CR)} = \frac{\text{Luminance measured when LCD on the "White" state}}{\text{Luminance measured when LCD on the "Black" state}}$$

Note 5: Definition of Luminance: Center Luminance of white is defined as luminance values of 1point average across the LCD surface.

Note 6: Definition of Color Chromaticity (CIE 1931)

Color coordinates of white & red, green, blue measured at center point of LCD.

Note 7: Definition of NTSC ratio:

$$\text{NTSC ratio} = \frac{\text{Area of RGB triangle}}{\text{Area of NTSC triangle}}$$



Note 8: Definition of optical measurement system.

The optical characteristics should be measured in dark room. After 5 minutes operation, the optical properties are measured at the center point of the LCD screen.(Response time is measured by Photo detector TOPCON BM-7, Field of view: 1°/Height: 500mm.)



7. RELIABILITY

Item 项目	Test Condition 测试条件	Remark 备注
High Temperature Storage	Ta =+80°C / 96Hours	Note1,2,3
Low Temperature Storage	Ta =-30°C / 96Hours	Note1,2,3
High Temperature Operating	Ta =+70°C / 96Hours	Note1,2,3
Low Temperature Operating	Ta =-20°C / 96Hours	Note1,2,3
Temperature Cycle storage Test	-30°C/30min ⇆+80°C /30min for 30cycles,Transfer time less than 5min	Note2,3
Thermal humidity storage Test	60°C x 90%RH / 96Hours	Note2,3
Package Vibration Test	Frequency: 10Hz~55Hz,Amplitude:1.5mm, 1 hrs for each direction of X, Y, Z	Note2
Packing shock test	Drop to the ground from 1m height, 1 corner, 3 edges, 6 surfaces.	Note2

Inspection after Test:

Note1:Ta is the ambient temperature of samples.

Note 2: In the standard condition, there shall be no practical problem that may affect the display function. After the reliability test, the product only guarantees operation, but doesn't guarantee all the cosmetic specification.

Note 3: Before cosmetic and function tests , the product must have enough recovery time, at least 2 hours at room temperature.

JIANGXI VIEWE TECHNOLOGY CO.,LTD

8. PACKAGE DRAWING